

Spectral Gamma-Ray Borehole Log Data Report

Page 1 of 2

Borehole

22-07-05

Log Event A

Borehole Information

Farm: \underline{BY} Tank: $\underline{BY-107}$ Site Number: $\underline{299-\underline{E33-116}}$

N-Coord : 45,860 **W-Coord** : 53,429 **TOC** Elevation : 649.83

Water Level, ft : Date Drilled : 7/23/1970

Casing Record

Type: Steel-welded Thickness: 0.280 ID, in.: 6

Top Depth, ft. : $\underline{0}$ Bottom Depth, ft. : $\underline{100}$

Borehole Notes:

According to the driller's records, this borehole was not perforated or grouted.

Equipment Information

Logging System : $\underline{1}$ Detector Type : \underline{HPGe} Detector Efficiency: $\underline{35.0~\%}$

Calibration Date : 03/1995 Calibration Reference : GJPO-HAN-1 Logging Procedure : P-GJPO-1783

Log Run Information

Log Run Number : 1 Log Run Date : 8/29/1995 Logging Engineer: Dave Traub

Start Depth, ft.: $\underline{97.0}$ Counting Time, sec.: $\underline{100}$ L/R: \underline{L} Shield: \underline{N} Finish Depth, ft.: $\underline{70.0}$ MSA Interval, ft.: $\underline{0.5}$ Log Speed, ft/min.: $\underline{n/a}$

Log Run Number :2Log Run Date :8/29/1995Logging Engineer:Dave Traub

Start Depth, ft.: $\underline{72.0}$ Counting Time, sec.: $\underline{100}$ L/R: \underline{L} Shield: \underline{N} Finish Depth, ft.: $\underline{0.0}$ MSA Interval, ft.: $\underline{0.5}$ Log Speed, ft/min.: $\underline{n/a}$



Spectral Gamma-Ray Borehole Log Data Report

Page 2 of 2

Borehole

22-07-05

Log Event A

Analysis Information

Analyst: S.E. Kos

Data Processing Reference : P-GJPO-1787 Analysis Date : 2/13/1996

Analysis Notes:

This borehole was logged in two log runs. The pre- and post-field verification spectra indicated that the logging system was operating properly during data collection. The energy/channel drift observed during the logging runs exceeded the search parameters of the processing software; therefore, multiple energy calibrations were required to process the data.

The casing thickness is 1/4 (0.250) in. The casing correction used to process the data was for 0.250-in. casing.

Cs-137 and Co-60 were the only man-made radionuclides detected. Cs-137 occurred from ground surface to a depth of about 31 ft, and at intermittent locations throughout the borehole. Co-60 occurred at depths from about 57 ft to TD, and intermittently within the depth interval from 35 to 55 ft.

Details regarding the interpretation of the data for this borehole are presented in the Tank Summary Data Report for tank BY-107.

Log Plot Notes:

Separate log plots show the man-made (e.g., Cs-137) and the naturally occurring radionuclides (K-40, U-238, and Th-232). The natural radionuclides can be used for lithology interpretations. The headings of the plots identify the specific gamma rays used to calculate the concentrations.

A combination plot includes both the man-made and natural radionuclides, in addition to the total gamma derived from the spectral data and the Westinghouse Hanford Company (WHC) Tank Farms gross gamma log. The gross gamma plot displays the latest available digital data from WHC with no attempt to adjust the depths to coincide with the SGLS data.

Uncertainty bars on the plots show the statistical uncertainties for the measurements as 95-percent confidence intervals. Open circles on the plots give the minimum detection level (MDL). The MDL of a radionuclide represents the lowest concentration at which positive identification of a gamma-ray peak is statistically defensible.